

EL-Dampgenerator fra 50 kg/h til 250 kg/h



TECHNICAL DATA

Model	Steam production kg/h	Power input kW	Standard Working pressure bar	Optional Working pressure * bar	Water content l
20	20	15	4.5	7	16
30	30	22	4.5	7	24
80	83	60	4.5	8.5	55
160	166	120	4.5	8.5	2 x 55
250	249	180	4.5	8.5	3 x 55

* higher working pressure available on request

DIMENSIONS

Model	W	L	H	Feed water	Blow down	Steam connection	Condensate return	Empty weight
	mm	mm	mm					kg
20	550	440	980	3/8"	1/2"	1/2"	1/2"	72
30	580	660	730	1/2"	1/2"	1/2"	1/2"	85
80	830	830	570	1/2"	1/2"	1/2"	1/2"	114
160	830	830	1395	1/2"	1/2"	1/2"	1/2"	237
250	1160	950	1670	1/2"	1/2"	1/2"	1/2"	325



I kan kontakte Jan Hansen på +45 21 22 28 50 og på jh@vh-as.dk

Vores produktområder

- Varmtvandskedler
- Dampkedler
- Varmepumper
- Elkedler
- Solfangere
- Olie- og gasbrændere
- PLC-løsninger / SRO-anlæg
- Stålskorstene
- Fjernvarmeanlæg
- Varmeflader - Køleflader
- Kraft/varmeanlæg
- Energiopsamling / Energistyring
- Røggasvekslere
- Reguleringsudstyr
- Tilbehør - reservedele
- Kedelreparationer
- Ollietanke
- Lyddæmpere
- Teknisk konsulentarbejde
- Service